

Quality Polymers from



25 Years of Innovation!

## RANTEC CORPORATION

PO Box 729  
Ranchester, WY 82839

Phone: (307) 655-9565

Fax: (307) 655-9528

www.ranteccorp.com

e-mail: rantec@ranteccorp.com

# EARTH TACK

## ANIONIC POLYACRYLAMIDE

### PRODUCT DESCRIPTION

**Earth Tack** is a premium polyacrylamide designed for hydromulching, hydroseeding, and dust control applications.

**Earth Tack** increases soil porosity and reduces sediment runoff through soil agglomeration and flocculating suspended sediment.

**Earth Tack** provides optimal slurry viscosity for ease of application.

**Earth Tack** provides for temporary erosion control during vegetative establishment.

### SPECIFICATIONS

Active Ingredient: Linear Co-Polymer of acrylamide and sodium acrylate  
Minimum Active Ingredient: 90%  
Ionic Charge: Anionic  
Molecular Weight: 16,000 – 20,000  
Environmental Certifications: ANSI/NSF Standard 60, contains less than 0.05% residual acrylamide

### APPLICATION RATE

For temporary erosion control, it is recommended that **Earth Tack** be applied at 6 to 8 lbs per 1000 gallons of water. The use of mulch at 150 to 300 lbs may be added as a marker.

SLOPE	FLAT	3:1	2:1	1:1
LB/ACRE	3-5	5-10	10-20	20-30

### PACKAGING

- 55 lb Bag
- 3 lb and 6LB Plastic Jug
- 3 lb LDPE Bag
- 3 lb Water Soluble Bag

**NEW WATER SOLUBLE BAGS!**

